



# Touch-Free. Oil-Free. Care-Free.

## TAMTURBO® AIR COMPRESSOR

- 2-stage models at 80–400 hp / 60–300 kW
- 3-stage models at 125–470 hp / 90–350 kW

## TECHNICAL INFORMATION

# Tamturbo® Touch-Free™ Compressors

## Touch-Free. Oil-Free. Care-Free.

### PRESSURE RANGE 5–9 BAR (75–130 PSI)

Model	Working Pressure		Free air delivery		Input power		Nominal power		Dimensions W/L/H)		Sound level dB(A)	Cooling
	bar	psi	m3/min	cfm	kW	hp	kW	hp	mm	inch		
TT145	5–9	75–130	8.0–20.2 12.8–28.0 10.4–28.4	290–720 460–990 370–1010	54–199	72–267	145	200	1821 2173 2059	71.7 85.6 81.1	76	Liquid / Air (optional)
TT185	5–9	75–130	14.2–33.0	510–1170	81–236	109–316	185	250	1821 2173 2059	71.7 85.6 81.1	76	Liquid / Air (optional)
TT225	5–9	75–130	20.5–37.6	730–1330	131–256	176–343	225	306	1821 2173 2059	71.7 85.6 81.1	76	Liquid / Air (optional)
TT325	5–9	75–130	22.5–53.3	800–1890	129–351	173–470	325	440	2489 2021 2022	98.0 79.6 79.6	76	Liquid / Air (optional)

### PRESSURE RANGE 2–5 BAR (30–75 PSI)

Model	Working Pressure		Free air delivery		Input power		Nominal power		Dimensions W/L/H)		Sound level dB(A)	Cooling
	bar	psi	m3/min	cfm	kW	hp	kW	hp	mm	inch		
TT115	2–5	30–75	6.6–20.3 10.4–28.1 8.5–28.4	240–720 370–1000 310–1010	30–145	41–194	115	155	1821 2173 2059	71.7 85.6 81.1	76	Liquid / Air (optional)
TT135	2–4.5	30–65	12.2–33.0	440–1170	47–155	63–207	135	180	1821 2173 2059	71.7 85.6 81.1	76	Liquid / Air (optional)
TT235	2–5	30–75	16.9–56.6	600–2000	63–246	84–329	235	320	2489 2021 2022	98.0 79.6 79.6	76	Liquid / Air (optional)

### ENERGY RECOVERY – STANDARD FEATURE

Cooling liquid outlet temperature 15–65 °C (60–150 °F)

Cooling liquid inlet temperature 5–35 °C (40–95 °F)

Ambient and inlet air temperature 5–40 °C (40–105 °F)

# RASTGAR

AIR COMPRESSORS

Call/Whatsapp +92 (334) 593-3391

io@rastgar-co.com

www.rastgar-co.com

This publication is for general informational purposes only and should not be construed as a representation or warranty on any subject matter, products or specifications. Tamturbo reserves the right at any time, without notice, to alter or discontinue the products and/or specifications referenced herein. This publication creates no warranty on the part of Tamturbo, express or implied, including but not limited to any implied warranty or merchantability or fitness for a particular purpose. Tamturbo is a registered trademark of Tamturbo Plc. Tamturbo Plc. reserves the right to make changes to product(s) described herein without prior notice. © Copyright Tamturbo Plc. 2019. Patents pending.

